

LONE STAR NGL LLC
PURITY PRODUCT SPECIFICATIONS

TABLE OF CONTENTS

UPDATED AS OF: MARCH 4, 2013

	ISSUING ENTITIES	PRODUCT	DATE
1.	Lone Star NGL Fractionators LLC Lone Star NGL Mont Belvieu LP	Ethane (Purity Ethane)	November 29, 2012
2.	Lone Star NGL Fractionators LLC Lone Star NGL Mont Belvieu LP	Propane	November 28, 2012
3.	Lone Star NGL Fractionators LLC Lone Star NGL Mont Belvieu LP	Isobutane	November 29, 2012
4.	Lone Star NGL Fractionators LLC Lone Star NGL Mont Belvieu LP	Normal Butane (Isom Grade)	November 29, 2012
5.	Lone Star NGL Fractionators LLC Lone Star NGL Mont Belvieu LP	Natural Gasoline	November 29, 2012
6.	Lone Star NGL Mont Belvieu LP	E/P Mix	November 16, 2012
7.	Lone Star NGL Mont Belvieu LP	Refinery Grade Butane	November 29, 2012

**ETHANE SPECIFICATION
(PURITY ETHANE)**

CHARACTERISTIC	PRODUCT SPECIFICATIONS	TEST METHOD
Corrosion, copper strip, maximum	1	ASTM D-1838
Total Sulfur, PPM by weight, maximum	30	ASTM D-6667
Analysis, L.V. %: Methane, maximum Ethane, minimum Ethylene, maximum Propane & Heavier, maximum	3.0 95.0 1.0 3.5	ASTM D-2163
Free water	None	Visual Inspection
Carbon Dioxide, PPM by weight, maximum	1000	ASTM D-2504

General Contaminants Note: The product shall be commercially free from sand, dust, gums, gum-producing substances, oil, glycol, inhibitors, amine, caustics, chlorides, oxygenates, heavy metals, any other contaminants that make it unfit for its commonly used applications and any compound added to the product to enhance the ability to meet these specifications.

Abbreviations: **ASTM** = American Society for Testing and Materials, Standard Test Procedures; **L.V. %** = liquid volumes percent; **PPM** = Parts per Million.

The aforementioned specifications may be modified from time to time in the sole discretion of the issuing entity.

PROPANE SPECIFICATION

CHARACTERISTIC	PRODUCT SPECIFICATIONS	TEST METHOD
Vapor Pressure (psig), maximum at 100° F	208	ASTM D-2598
Relative Density at 60° F /60° F Minimum Maximum	.500 .510	ASTM D-1657
Volatile Residue, temperature @ 95 L.V. % evaporated, maximum	-37° F	ASTM D-1837
Residual Matter: Residue on evaporation of 100 ml., maximum ml. Oil stain (Note 1)	0.05 Pass	ASTM D-2158
Corrosion, copper strip, maximum	1	ASTM D-1838
Total Sulfur, PPM by weight, maximum	123	ASTM D-6667
Fluorides, PPM by weight, maximum	1	ASTM D-7359
Analysis, L.V. % Propane, minimum Propylene, maximum Butanes and heavier, maximum	90.0 5.0 2.5	ASTM D-2163
Free water	None	Visual Inspection

Note 1: An acceptable product shall not yield a persistent oil ring when 0.3 ml of solvent residue is added in 0.1 increments, after examination in daylight after 2 minutes as described in ASTM D-2158.

General Contaminants Note: The product shall be commercially free from sand, dust, gums, gum-producing substances, oil, glycol, inhibitors, amine, caustics, chlorides, oxygenates, heavy metals, any other contaminants that make it unfit for its commonly used applications and any compound added to the product to enhance the ability to meet these specifications.

Abbreviations: ASTM = American Society for Testing and Materials, Standard Test Procedures; ° F = Degrees Fahrenheit; L.V. % = liquid volume percent; ml = milliliters; PPM = Parts per Million; psig = pounds per square inch gauge.

The aforementioned specifications may be modified from time to time in the sole discretion of the issuing entity.

ISOBUTANE SPECIFICATION

CHARACTERISTIC	PRODUCT SPECIFICATIONS	TEST METHOD
Corrosion, copper, maximum	1	ASTM D-1838
Total Sulfur, PPM by weight, maximum	140	ASTM D-6667
Analysis, L.V. % propane, maximum isobutane, minimum	3.0 96.0	ASTM D-2163
Free water	None	Visual Inspection

General Contaminants Note: The product shall be commercially free from sand, dust, gums, gum-producing substances, oil, glycol, inhibitors, amine, caustics, chlorides, oxygenates, heavy metals, any other contaminants that make it unfit for its commonly used applications and any compound added to the product to enhance the ability to meet these specifications.

Abbreviations: **ASTM** = American Society for Testing and Materials, Standard Test Procedures; ° **F** = Degrees Fahrenheit; **L.V. %** = liquid volume percent; **PPM** = Parts per Million.

The aforementioned specifications may be modified from time to time in the sole discretion of the issuing entity.

**NORMAL BUTANE SPECIFICATION
(ISOM GRADE)**

CHARACTERISTIC	PRODUCT SPECIFICATIONS	TEST METHOD
Corrosion, copper strip, maximum	1	ASTM D-1838
Total Sulfur, PPM by weight, maximum	140	ASTM D-6667
Volatile Residue, temperature @ 95 L.V. % evaporated, maximum	+36° F	ASTM D-1837
Fluorides, PPM by weight, maximum	1.4	ASTM D-7359
Analysis, L.V. %		
Propane, maximum	0.35	ASTM D-2163
Isobutane, maximum	6.0	
Normal Butane, minimum	94.0	
Pentanes and Heavier, maximum	1.5	
Butadiene, maximum	0.01	
Total Olefins, maximum	0.35	
Free water	None	Visual Inspection
Vapor Pressure, psig, maximum at 100 ° F	50	ASTM D-1267

General Contaminants Note: The product shall be commercially free from sand, dust, gums, gum-producing substances, oil, glycol, inhibitors, amine, caustics, chlorides, oxygenates, heavy metals, any other contaminants that make it unfit for its commonly used applications and any compound added to the product to enhance the ability to meet these specifications.

Abbreviations: **ASTM** = American Society for Testing and Materials, Standard Test Procedures; ° **F** = Degrees Fahrenheit; **L.V. %** = liquid volume percent; **PPM** = Parts per Million.

The aforementioned specifications may be modified from time to time in the sole discretion of the issuing entity.

NATURAL GASOLINE SPECIFICATION

CHARACTERISTIC	PRODUCT SPECIFICATIONS	TEST METHOD
Gravity, API	Report	ASTM D-287
Vapor Pressure, psia, maximum	14.0	ASTM D-6378
Color, Saybolt, minimum	+25	ASTM D-156
Doctor Test	Negative	ASTM D-4952
Existent Gum, mg/100 ml maximum (washed)	4.0	ASTM D-381
Total Sulfur, wt. %, maximum	0.1	ASTM D-6667
Octane Numbers (Note 1) Research Motor (R+ M)/2	Report Report Report	ASTM D-2699 ASTM D-2700
Distillation, temperature 10%, evaporated 50% evaporated 70% evaporated, minimum 90% evaporated, maximum end point	Report Report 140° F 275° F 375° F	ASTM D-7344

Note 1: Lone Star NGL LLC and its subsidiaries (“LST”) reserves the right to refuse to receive, store or transport any natural gasoline if the octane of said natural gasoline is not consistent with that of the natural gasoline then in the storage/pipeline inventory in the LST systems.

General Contaminants Note: The product shall be commercially free from sand, dust, gums, gum-producing substances, oil, glycol, inhibitors, amine, caustics, chlorides, oxygenates, heavy metals, any other contaminants that make it unfit for its commonly used applications and any compound added to the product to enhance the ability to meet these specifications.

Abbreviations: ASTM = American Society for Testing and Materials, Standard Test Procedures; ° F = Degrees Fahrenheit; mg = milligrams; ml = milliliters; PPM = Parts per Million; psia = pounds per square inch absolute; wt. % = percentage by weight.

The aforementioned specifications may be modified from time to time in the sole discretion of the issuing entity.

ETHANE-PROPANE MIX SPECIFICATION

CHARACTERISTIC	PRODUCT SPECIFICATIONS	TEST METHOD
Corrosion, copper strip, maximum	1	ASTM D-1838
Total Sulfur, PPM by weight, maximum	123	ASTM D-6667
Analysis, L.V. %: Methane, maximum (Note 1) Ethane, maximum (Note 2) Propylene, maximum Butanes and Heavier, maximum Carbon Dioxide, maximum	1.5 75.0 5.0 2.5 0.2	ASTM D-2163
Free water	None	Visual Inspection

Note 1: 3.0 L.V. % allowed, provided total ethane (methane included) does not exceed 75.0 L.V. %

Note 2: 80.0 L.V. % maximum ethane allowed (methane included), provided the methane does not exceed 1.5 L.V. %.

General Contaminants Note: The product shall be commercially free from sand, dust, gums, gum-producing substances, oil, glycol, inhibitors, amine, caustics, chlorides, oxygenates, heavy metals, any other contaminants that make it unfit for its commonly used applications and any compound added to the product to enhance the ability to meet these specifications.

Abbreviations: **ASTM** = American Society for Testing and Materials, Standard Test Procedures; **L.V. %** = liquid volume percent; **PPM** = Parts per Million.

The aforementioned specifications may be modified from time to time in the sole discretion of the issuing entity.

REFINERY GRADE BUTANE SPECIFICATION

CHARACTERISTIC	PRODUCT SPECIFICATIONS	TEST METHOD
Corrosion, copper strip, maximum	1	ASTM D-1838
Total Sulfur, PPM by weight, maximum	140	ASTM D-6667
Volatile Residue, temperature @ 95 L.V. % evaporated, maximum	+36° F	ASTM D-1837
Fluorides, PPM by weight, maximum	150	ASTM D-7359
Analysis, L.V. %		
Propane, maximum	2.5	ASTM D-2163
Normal Butane, minimum	94.0	
Isobutane, maximum	6.0	
Pentanes and Heavier, maximum	2.0	
Free water	None	Visual Inspection

General Contaminants Note: The product shall be commercially free from sand, dust, gums, gum-producing substances, oil, glycol, inhibitors, amine, caustics, chlorides, oxygenates, heavy metals, any other contaminants that make it unfit for its commonly used applications and any compound added to the product to enhance the ability to meet these specifications.

Abbreviations: **ASTM** = American Society for Testing and Materials, Standard Test Procedures; ° **F** = Degrees Fahrenheit; **L.V. %** = liquid volume percent; **PPM** = Parts per Million.

The aforementioned specifications may be modified from time to time in the sole discretion of the issuing entity.